

### Industrial / Spectacles / 5X1

# 5X1 - Contrast

Code: 5X1.00.00.03 Date: 09-08-25 1/2

Multifunctional and versatile, the 5X1 was created to guarantee optimal protection in any working condition. On one frame it's possible to assemble a wide range of interchangeable accessories, ensuring every worker can personalise the 5X1 without compromising comfort and protection. The extended wraparound lenses provides extra coverage around the eyes.



Frame mark (EU
----------------

Mod5X1 U 166 FT U 175-F

#### Lens mark (EU)

2C-1.2 U 1 FT CE

### Frame technology

Interchangeable Lens, Nose pad set-up, Floating Lens, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal, Terminal tilting movement, SoftPad

Conditions of use	Lens technology	Lens color
Cloud, Fog	Anti-Scratch, Anti-Fog, UV400	Yellow
Lens material	Frame color	Standards
Polycarbonate	Dark grey/Green	EN166, EN170
Scale number	Mechanical resistance	Optional requirements
(2C-1.2)	Low energy impact (F)	Protection against high speed particles at extreme temperatures -5°/+55° C (T)
Optical class	Weight	
Optical class (1)	28g	

### Industrial / Spectacles / 5X1

>> https://www.univetsafety.com/en/products/safety/spectacles/5x1/5x1-contrast/



01.

#### NOSE PAD SET-UP

Allows to adjust the height of the glasses to ensure maximum optical quality

02.

#### LENS INTERCHANGE SYSTEM

Thanks to the patent lens exchange system it is possible to quickly replace the lens for optimal visibility in any environment

03.

# RUBBER TERMINAL WITH INCLINATION MOVEMENT

Allows the glasses to adhere to the temples for a perfect grip

04.

## INCLINATION AND LENGTH ADJUSTMENT

Allows correct fitting and constant safety at work

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.