

**Frame mark (EU)**

U EN166 3 4 5 9 BT 2C-3 CE

Lens mark (EU)

2C-1.2 U 1 BT 9 K N CE

Frame technology

Interchangeable Lens, Interaction among PPE - Nexxt

Conditions of use

Standard brightness, Low brightness

Fields of use

Liquids (3), Large dust particles (4), Gas and fine dust particles (5), Molten metals and hot solids (9)

Lens technology

Anti-Scratch (K), Anti-Fog (N), UV380

Lens color

Clear

Lens material

Polycarbonate

Frame color

Red

Standards

EN166, EN170

Scale number

(2C-1.2), (2C-3)

Mechanical resistance

Medium energy impact (B)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Optical class

Optical class (1)

Weight

122g

>> <https://www.univetsafety.com/en/products/safety/goggles/611/611-clear/>



01.

WIDE ELASTIC BAND WITH SILICONE
INSERTS IMPROVES STABILITY

02.

THE DOUBLE LENS WITH THERMAL
BREAKAGE TECHNOLOGY PROTECTS
AGAINST HEAT, FOGGING AND
IMPACTS

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163